radaway [L]				DW-06L
CUSTOMER DATA:			MOUNTING PROFILES:	L R
			COMPLIES WITH SERIES AND MOD	PELS
SERIES AND MODEL:	INSTALLER DATA:		OTHER:	
FITTINGS COLOR:				
GLASS COLOR:			OTHER:	
MEASUREMENT METHODS:				
	[V V []			<u></u>
X - niche Y X - niche Y X	X - niche Y	X - niche Y	X - niche Y	X - niche Y
WEM AKP	AKG	GMF	IKG	IKP
				100
MAIN DRAWING	CONSTRUCTION HEIGHT AT "0" POINT:			
		STANDARD	OTHER:	
ENTRANCE: X SIDE			OTTIEN	
MEASURE AND GIVE DEVIATIONS: (A BLANK FIELD MEANS NO DEVIATION)				
			L DEVIATIONS. (A BLANK FILLD IV	ILMO DEVIATION)

Υ DW1 DW2 DR Q2 CHOOSE THE VARIANT OF THE LAYOUT: Q1 *X 🔲 R * DIMENSIONS ACCORDING TO THE MAIN DRAWING X [**DETAIL A** GIVE DIMENSIONS AND METHOD OF INTERPRETATION: w X S1 S2 **S3**

⚠ ATTENTION, RADAWAY, FOR TECHNOLOGICAL REASONS, RESERVES THE POSSIBILITY OF MAKING CONSTRUCTION CHANGES.

REMARKS: _

S4

^{*}INDICATE "0" POINT(S) AND SEPCIFY DEVIATION(S) AS A NEGATIVE VALUE POINT(S) "0" IS/ARE THE HIGHEST POINT(S) ON THE FLOOR / SHOWER TRAY / L-SHAPE WALL

 $^{^{\}star\star}$ CHECK THE FLATNESS AND DESCRIBE ANY CURVES. STANDARD GAP IS 3 MM, CONSIDER INCREASING IT.