



CUSTOMER DATA: _____
 SERIES AND MODEL: _____ INSTALLER DATA: _____
 FITTINGS COLOR: _____
 GLASS COLOR: _____

MOUNTING PROFILE:	Q	Y
COMPLIES WITH SERIES AND MODELS	<input type="checkbox"/>	<input type="checkbox"/>
OTHER:	<input type="checkbox"/>	<input type="checkbox"/>
OTHER:	<input type="checkbox"/>	<input type="checkbox"/>

MEASUREMENT METHODS: ENTRANCE SIDE „X” SIDE „Z”



MAIN DRAWING





CONSTRUCTION HEIGHT AT "0" POINT:

STANDARD OTHER:
 NO POSSIBILITY TO CHANGE THE HEIGHT

MEASURE AND GIVE DEVIATIONS (A BLANK FIELD MEANS NO DEVIATION)

DL + - 0
 DW - + 0
 DR - + 0

CHOOSE THE VARIANT OF THE LAYOUT OF THE BUILDING WALLS FOR X, Y, Z;



* INDICATE "0" POINT(S) AND SPECIFY DEVIATION(S) AS A NEGATIVE VALUE
 POINT(S) "0" IS/ARE THE HIGHEST POINT(S) ON THE FLOOR / SHOWER TRAY / L-SHAPE WALL
 W1, W2 TO BE MEASURED FROM THE SHOWER ENCLOSURE BASE

** CHECK THE FLATNESS AND DESCRIBE ANY CURVES. STANDARD GAP IS 3 MM,
 CONSIDER INCREASING IT.

GIVE DIMENSIONS AND INTERPRETATION METHODS

	X	Y	Z
S1			
S2			
S3			
S4			

 ATTENTION, RADAWAY, FOR TECHNOLOGICAL REASONS, RESERVES THE POSSIBILITY OF MAKING CONSTRUCTION CHANGES.

REMARKS: _____