radaway 🔲	VN_151
·	KN-15L
CUSTOMER DATA:	MOUNTING PROFILE: X Y  COMPLIES WITH SERIES AND MODELS
SERIES AND MODEL: INSTALLER DATA:	OTHER:
FITTINGS COLOR:	
GLASS COLOR:	OTHER:
MEASUREMENT METHODS: ENTRANCE: 5	IDE "X" SIDE "Y"
X Y X Y AKP AKG	X Y X Y X Y IKP
MAIN DRAWING	CONSTRUCTION HEIGHT AT "0" POINT:
ENTRANCE: SIDE "X"	STANDARD OTHER:
₩	MEASURE AND GIVE DEVIATIONS (A BLANK FIELD MEANS NO DEVIATION)
The state of the s	DR  DR  DW1  DW2  DW2  DW2
	CHOOSE THE VARIANT OF THE LAYOUT OF THE BUILDING WALLS FOR X AND
DETAIL A	*X
DETAIL B	X
*	GIVE DIMENSIONS AND METHOD OF INTERPRETATION:
B**	X
	S1
T W	
*	52

\*INDICATE "0" POINT(S) AND SEPCIFY DEVIATION(S) AS A NEGATIVE VALUE
POINT(S) "0" IS/ARE THE HIGHEST POINT(S) ON THE FLOOR / SHOWER TRAY / L-SHAPE WALL
\*\* CHECK THE FLATNESS AND DESCRIBE ANY CURVES. STANDARD GAP IS 3 MM, CONSIDER INCREASING IT.

ATTENTION, RADAWAY, FOR TECHNOLOGICAL REASONS, RESERVES THE POSSIBILITY OF MAKING CONSTRUCTION CHANGES.

REMARKS: -